



## 48V 150Ah 7.8KWh LFP Battery Rack Mounted LifePO4 Lithium Battery with RS485 Communication Port

Our Product Introduction

### Basic Information

- Place of Origin: Hubei, China
- Brand Name: SYEV/OEM/ODM
- Certification: CE FCC
- Model Number: SY48100F1-3U
- Minimum Order Quantity: 10pcs
- Price: USD300~500
- Packaging Details: Carton
- Delivery Time: 5~8 work days
- Payment Terms: L/C, T/T, Western Union
- Supply Ability: 1000pcs/month



### Product Specification

- Product Type: Lifepo4 Lithium Battery
- Nominal Voltage: 51.2V
- Nominal Capacity: 150Ah
- Nominal Capacity (KWh): 7.68KWh
- Cycle Life:  $\geq 6000$  Cycles @0.3C/0.3C
- Communication Port: RS485/CAN
- Charge Voltage(V): 57.6V
- Charge Current(A): 30A(Recommend)
- Charge Temperature: 0 To 55
- Battery Size: 483mm\*450mm\*177mm
- Pack Weight: 63kg
- Highlight: **7.8KWh LFP Battery,  
Rack Mounted LifePO4 Lithium Battery,  
RS485 Communication Port LFP Battery**

for more products please visit us on [battery-generator.com](http://battery-generator.com)

## Product Description

### 48V 150Ah 7.8KWh LFP Battery Rack Mounted LifePO4 Lithium Battery with RS485 Communication Port

#### Products Detailed Specification

Electrical Characteristics		Charging Parameters	
Nominal Voltage (V)	51.2V	Charge Voltage(V)	57.6V
Nominal Capacity(Ah)	150Ah@0.3C	Charge Current(A)	30A(Recommend)
Nominal Capacity (KWh)	7.68KWh	Max Charge Current(A)	50A
Cycle Life	≥6000 Cycles @0.3C/0.3C	Peak Charge Current(A)	100A
Serial Number	16S1P		
Commnication Port	RS485/CAN	Charging Mode	Constant Current/ Constant Voltage
Discharge Parameters		Operating Environment	
Discharge Cut-off Voltage	46.4V	Charge Temperature	0 to 55
Discharge Current	50A(Recommended)	Discharge Temperature	-20 to 60
Max Discharge Current	100A	Storage Temperature	0 to 40

#### Using Note:

1. The charging voltage of the battery shall not exceed the parameters in the specification
2. When the battery is in use, the discharge voltage shall not be lower than the parameters in the specification, otherwise the low voltage protection may be triggered
3. The charging current and discharging current of the battery shall not exceed the parameter range of the specification, otherwise the battery may be damaged

#### Product HD picture





#### Product Features:

# 12V SERIES Big Capacity LifePO4 Battery

专业定制应用广泛

VARIOUS

SMALL SIZE

LONG LIFE



PRODUCT 12V50AH



PRODUCT 12V150AH



PRODUCT 12V200AH



PRODUCT 12V250AH



PRODUCT 12V300AH

科技·创新  
NEW ENERGY RESOURCES  
强劲性能 新能源

## 12.8V SERIES Solutions Customized

Choosing us is equal to choosing protection



Factory Tourist

# 源头实力厂家

12 YEARS SOURCE STRENGTH FACTORY

十多年来专注锂电池质造，开发定制

FOCUSED ON LITHIUM BATTERY MANUFACTUREING AND CUSTOMIZED



HaiNan SynYune EV Technology Co.,Ltd



SYJackie@163.com



battery-generator.com

No. 4 Jipu Road, Xinyingwan District, Yangpu EDZ, Hainan Province